


[Home](#)
[Stump Grinders](#)
[Cranes](#)
[Chippers](#)
[Inventory](#)

HAWK Stump Grinder Specifications - Standard Model

Engine

13-HP Honda with Recoil Start & Cyclone Air Cleaner
 20-HP Honda with Electric Start & Cyclone Air Cleaner
 13-HP Kohler with Recoil Start
 20-HP Kohler with Electric Start
 Low oil pressure shutdown with splash lubrication
 1.72-gallon fuel tank

Cutter Wheel

14" diameter x 3/8" thick
 1,575 RPM when engine is at 2,500 RPM
 1-1/2" diameter cutter wheel shaft
 1-3/16" self-aligning pillow block bearings
 3V grooved HI POWER banded belt
 Fully-enclosed 14 ga. steel belt guard secured to frame (not engine)
 8 reversible pockets
 8 individual carbide teeth with 1/2" square shank

Manual

Manual is located in a weatherproof Manual Pack mounted on the handle bar and attached with a steel tether. This ensures that the manual stays with the unit and the operator can review the operational instructions at any time. A second manual is included with each unit and is also available on a cd-rom.

General

30-1/2" wide



Height Position	Handle Bar Height	Length to End of Handle Bar
1 (lowest)	42-1/2"	98-3/4"
2nd	46-7/8"	96-1/2"
3rd	51-7/8"	93-3/4"
4th	54-3/4"	89-1/2"
5th	57-7/8"	85-1/4"
6th (highest)	60"	80-1/2"

Height to top of engine: 34"

Weight: 320 pounds (varies w/engine selection)

Frame: 7 gauge hot-rolled steel channel

Handle Bar: heavy-duty 1-5/16" steel pipe

Tires: high speed 4.80-8"

Brakes: drum type brake on right wheel, hand engaged with easy-to-reach lever on handle bar

Cutting Range

Any diameter, no limitations; 24" above ground; 16" below ground

Options:

- Quick-disconnect towing package with 2" ball
- Green wheel for sharpening teeth

Specifications subject to change without notice or obligation.

Specifications - Self-Propelled Model

Engine

20-HP Kohler or Honda with Electric Start
 25-HP Kohler or Honda with Electric Start
 Low oil pressure shutdown
 Heavy duty industrial cartridge-type air filter

Cutter Wheel

14" diameter x 3/8" thick
 1,575 RPM when engine is at 2,500 RPM
 1-1/2" diameter cutter wheel shaft
 1-3/16" self-aligning pillow block bearings
 8 reversible pockets
 8 individual carbide teeth with 1/2" square shank

Cutting Range

Any diameter, no limitations
 24" above ground; 16" below ground

Drive Train

Hydrostatic drive and transaxle with disc brake

Fully-enclosed 14 ga. steel belt guard secured to frame (not engine)
 2V Grooved HI POWER belts, A section banded
 Infinitely variable speed control
 Positive mechanical drive belt adjustment
 Positive locking free-wheel position

Options:

Green wheel for sharpening teeth

General

Width: 32"

Height to top of engine: 42"

Weight: 550 pounds (varies w/engine selection)

Frame: 7 gauge hot-rolled steel channel; all welds continuous

Handle Bar: heavy-duty 1-5/16" steel pipe; 7 position handle bar yields size range from 101" length and 39" height (lowest position) to 78" length and 61" height (highest position)

Tires: 6.50 x 16" Super Lug Traction Mudder mounted on *removeable wheel* with 4-bolt hub

Brakes: disc brakes, hand engaged with easy-to-reach lever on handle bar. Return spring ensures non-stick release

Gas Tank: 3-gallon marine style UL approved

Battery: Heavy duty 340 CCA battery in completely enclosed steel battery box

PTO: Electric PTO

Throttle: Positive locking veneer type throttle cable

Manual

Manual is located in a weatherproof Manual Pack mounted on the handle bar and attached with a steel tether. This ensures that the manual stays with the unit and the operator can review the operational instructions at any time. A second manual is included with each unit and is also available on CD-ROM.

Specifications subject to change without notice or obligation.



[Home](#) | [Hawk Stump Grinder](#) | [HAWK Self-Propelled Model](#) | [HAWK Stump Grinder Features](#)
[HAWK Stumpgrinder Specifications](#) | [HAWK Stump Grinder News](#) | [Magnum Cranes](#) | [Woodchuck Chippers](#) | [Inventory](#)

HAWK Equipment Corporation 14118 Fairgate Boulevard Newbury, OH 44065

Toll Free: 1-877-591-5855 • Phone: 1-440-564-1499 • info@hawkequipmentcorp.com