



(/)

(tel: +18665815

You are here: Home (<https://www.everythingattachments.com/>) > Browse Machinery (<https://www.everythingattachments.com/category-s/10654.htm>) > Browse by Tractor (<https://www.everythingattachments.com/browse-attachments-by-tractor-s/3786.htm>) > John Deere Tractor Attachments (<https://www.everythingattachments.com/John-Deere-Tractor-Attachments-for-any-John-Deere-s/3790.htm>) > 30-39 hp John Deere Tractors (<https://www.everythingattachments.com/category-s/3813.htm>) > John Deere 4500 (<https://www.everythingattachments.com/John-Deere-4500-Attachments-specs-s/4095.htm>)

John Deere 4500 Tractor



What we know about the John Deere 4500 tractor is that it has a 4 cylinder Diesel Engine that produces 39 horsepower. Shown left is a picture of the John Deere 4500 tractor.

The John Deere 4500 tractor has a category 1 three point hitch and its pto is rated at 33 hp. This John Deere tractor has power steering and is offered in 2WD, and optional 4X4 MFWD 4WD. View entire John Deere 4500 specifications below.

Please click the button or scroll down to find our recommended **John Deere 4500 Attachments**.



General tractor information:

Manufacturer:	John Deere
Model:	4500
Type:	Farm/Agricultural tractor
Total built:	-unknown-
Factory:	-unknown-
Original price:	\$18,000 (2000)

Tractor power:

Engine:	39 hp [29.1 kW]
PTO (rated):	33 hp [24.6 kW]

Engine:

Manufacturer:	Yanmar
Model:	4TNE84
Fuel:	diesel
Cylinders:	4
Bore/Stroke:	3.30x3.50 inches [84 x 89 mm]
Displacement:	122 cu ft 3.0 L

Displacement:	122 ci [2.0 L]
Horsepower:	39 hp [29.1 kW]
Compression:	18:1
Rated RPMs:	2600
Cooling:	liquid
Coolant:	7.6 qts [7.2 L]
Torque:	125 lb-ft [169.5 Nm]
Torque RPMs:	1700
Firing order:	-unknown-
Oil capacity:	5.1 qts [4.8 L]

Transmission:

Type:	collar shift
Forward:	9
Reverse:	3
Capacity:	27.2 qts [25.7 L]

Transmission:

Type:	PowerReverser
Forward:	12
Reverse:	12
Capacity:	27.2 qts [25.7 L]

Mechanical:

Chassis:	4x2 2WD 4x4 MFWD 4WD optional
Steering:	power
Steering pump flow:	4.8 gpm [18.2 lpm]
Brakes:	wet disc

Capacity:

Fuel:	12.5 gal [47 L]
-------	-----------------

3-Point Hitch:

Rear Hitch Category:	1
Rear lift:	-unknown-
Rear lift (at 24"/610mm):	2,500 lbs [1134 kg]

Power Take-off (PTO):

Rear PTO:	independent
Rear speed (RPM):	540
Mid PTO:	independent
Mid speed (RPM):	2100

Hydraulics:

Type:	open center
Capacity:	6.8 gal [25.7 L]

Capacity:	6.6 gal [25 L]
Total flow:	14.7 gpm [55.6 lpm]
Valve flow:	9.9 gpm [37.5 lpm]
Pressure:	2500 psi [172.4 bar]
Valves:	3 optional

Tires:

Ag front:	6.00-16
Ag rear:	13.6-24

Dimensions:

Weight:	3,450 lbs [1564 kg]
Wheelbase:	71.5 inches [181 cm]
Length:	135 inches [342 cm]
Width:	62 inches [157 cm] (R1 tires)
Height:	51 inches [129 cm] (hood) 97.6 inches [247 cm] (ROPS)
Ground clearance:	-unknown-

Electrical:

System:	alternator
Amps:	40

Battery:

Number:	1
Cold-cranking amps:	650
Volts:	12

OUR RECOMMENDED ATTACHMENTS FOR THIS TRACTOR**Sort By:**

Price: Low to High ▼

Go

90 per page ▼

1



(<https://www.everythingattachments.com/Attachments-Low-Profile-Standard-Bkt-p/cal-bucket-gp-stand-lp-1gpsb.htm>)



(<https://www.everythingattachments.com/Construction-Attachments-4-in-1-Low-Capacity-Bkt-p/cal-bucket-mp-lc-4in1-1mplc.htm>)



(<https://www.everythingattachments.com/Attachments-XTreme-Grapple-Bucket-p/cal-grapple-bucket-xt.htm>)