

# SPECS

## SVL75-2W

### SPECIFICATION

### DETAIL

#### MODEL

---

**Model Name**

SVL75-2HFWC

---

#### ENGINE

---

**Make**

Kubota

---

**Model**

V3800CR-TIE F4

---

**Displacement**

---

**Cylinders**

Four

---

**Bore and stroke in. (mm)**

---

**Aspiration**

Turbocharged

---

#### LOADER PERFORMANCE

---

**Rated operating capacity-35% tipping load lbs. (kg)**

2300 (1043)

---

**Rated operating capacity-50% tipping load lbs. (kg)**

3285 (1490)

---

**Tipping load lbs. (kg)**

6570 (2980)

---

**Breakout force**

Bucket lbf. (kg)	6204 (2814)
------------------	-------------

Lift arm lbf. (kg)	4766 (2162)
--------------------	-------------

<b>Lift arm path</b>	Vertical
----------------------	----------

**UNDERCARRIAGE****Track Width**

Standard in. (mm)	12.6 (320)
-------------------	------------

Wide in. (mm)	15.0 (380)
---------------	------------

**Ground pressure**

Standard psi	5.6 / 5.8
--------------	-----------

Wide psi	4.7 / 4.9
----------	-----------

<b>Track ground contact length in. (mm)</b>	56.5 (1436)
---	-------------

<b>Track rollers (per side)</b>	4
---------------------------------	---

**Travel speed**

Low mph (km/h)	4.7 (7.5)
----------------	-----------

High mph (km/h)	7.1 (11.5)
-----------------	------------

**HYDRAULIC SYSTEM****Aux. hydraulic flow**

High flow gpm (l/min)	29.3 (110.9)
-----------------------	--------------

Std. gpm (l/min)

17.4 (66.0)

**Aux. hydraulic pressure psi (kgf/cm2)**

3185 (224.0)

**SERVICE REFILL CAPACITIES****Hydraulic system gal. (l)**

15.9 (60)

**Hydraulic tank gal. (l)**

9.2 (35)

**Fuel tank gal (l)**

24.6 (93)

**OTHER****Operating weight (Includes operator weight 165lbs.) lbs.  
(kg)**

9083 (4120) / 9359 (4245)