BROCE BROOM MODEL BB-250-B SPECIFICATIONS

Standard Equipment on All Units

- Safety orange paint
- 8' steel core with 6 3/8" x 24" poly flat wafers
- Electric over hydraulic brush lock
- Certified roll-over protection structure and canopy ISO 3471 Compliant
- Seat Belts ISO 6683 Compliant
- Power steering
- 2-wheel hydraulic drum brakes with manual parking brake
- 16 gauge core cover
- 72 gallon water sprinkler system
- 2" ball tow hitch with surge brakes and tow lights
- · Hydraulic tow hitch
- Gauge package includes: oil, water, alternator, fuel and hour meter
- P185/70R14" radial tires
- Sauer Danfoss hydrostatic
- Wheel Drive hydraulic motors
- · Single direct drive motor on brush drive
- Broom controls two spool joystick valve with adjustable down pressure and float position
- Steering orbital type steering w/dead steer capabilities
- · Padded seat with arm rests and seat belt
- Reverse alarm

Optional Equipment

- 6' core (in lieu of std. 8')
- 2 5/16" ball hitch or pintle eye hitch
- · Amber beacon light
- Amber strobe light
- Front work lights and rear tail lights
- Rear work lights (2 single beam)
- Hitch disconnect warning light
- Paint (other than standard safety orange)
- Engine shutdown safety system
- Windshield
- Traffic horn



	
Dimensions	Height 7'10" Width 8'
	Length 12'6"
Engine - Kubota or Caterpillar diesel	Kubota 24 HP - Tier 4
Machine Weight	3,000 lb.
Weight w/Water System	3,600 lb.
Broom Size	6 3/8" ID x 24" OD
Broom Length	Full 8' (Optional 6')
Broom Drive	Single Hydraulic Motor
Brush Speed	192 RPM
Broom Angle	Full 40 Degrees
	(both ways)
Steering	60 Degrees
	(both ways)
Outside Turning Radius	10' 9"
Inside Sweeping Radius	5'
Fuel Capacity	9 U.S. gallon
Hydraulic Oil Capacity	15 U.S. gallon
Speed	0 to 10 mph

Distributed by:



Sales: 866-579-2488 • Parts & Service: 877-227-8811